



MUTUAL INDUSTRIES, INC.
707 W. GRANGE
PHILADELPHIA, PA 19120
215-927-6000 * 800-523-0888
215-927-3388 FAX
www.mutualindustries.com

#3200-6-60
5' X 50' TURBIDITY CURTAIN
TYPE 1 DOT SPECIFICATION

18oz. Laminated vinyl/polyester fabric meets the following specification:

CONSTRUCTION	Vinyl Laminate on 1300 Denier 9x9 scrim	
WEIGHT	18oz. / sq.yd	ASTM D-2374
ADHESION	15 lb / inch	ASTM D-751-95 Sec. 43.1.2
GRAB TENSILE	397 x 373 lb / inch	ASTM D-5034
TOUNG TEAR	96 x 86 lb / inch	ASTM D-2261
HYDROSTATIC	385 psi	ASTM D-751-95 Sec 34.2

ADDITIONAL PRODUCT SPECIFICATIONS

- Heat sealed seams
- 5/8" polypropylene twisted rope edge reinforcement
- 6"x6"x48" EPS foam blocks providing 11 lbs / ft buoyancy
- Standard depth = 5 feet
- #4 brass grommets approximately 12" o.c. in edges for laced connection
- Aluminum stress plates at top and bottom corners
- 1/4" galvanized steel ballast chain